

---

 **Back**

---



## AFI®/SP16VAL 30Y

Mandrel built cooling water delivery hose with insulating rubber for the steel industry. Delivered in fix lengths and equipped with built-in couplings and flanges

UNI - DIN - ANSI B 16.5. The hose is insulating > 109 Ohm and the flanges at the ends are electrically insulated.

Technical characteristics

REQUEST INFORMATION

## CHOOSE YOUR SIZE

76 mm

100 mm

125 mm

250 mm

Inner diameter 76 mm

Weight 4,75 Kg/m

Vacuum 0.8 bar

Bending Radius 450 mm

REQUEST QUOTE

## Related products

You may also be interested in these products



HEXAGON



TETRAGON



AFI®/20B 32W



AFI®/SP16L 39W

Didn't find  
what you were  
looking for?

Click here to reach out our customer support team for assistance on the range or for the design of your custom-made product.

[CONTACT US](#)

# Do you need more information?

Contact us!



NAME\*

SURNAME\*

EMAIL\*

COMPANY NAME\*

MOBILE\*

COUNTRY\*

MESSAGE\*



I have read and agree to the [privacy policy](#) of this site.

SEND

Tubi Thor S.p.A.  
Industrial Rubber Hoses

Registered Head office  
Via Manzoni, 43  
Milan (MI) - Italy

Headquarter  
Via Caduti per la Patria, 83  
Lesmo (MB) - Italy  
+39 039-6064616  
info@thor-group.it  
Vat: IT00755050150  
Iscr.Uff.Reg. Imprese REA: 569348

|                          |                                |
|--------------------------|--------------------------------|
| <a href="#">Company</a>  | <a href="#">News</a>           |
| <a href="#">Quality</a>  | <a href="#">Contacts</a>       |
| <a href="#">Products</a> | <a href="#">Whistleblowing</a> |

Thor Hoses © 2025, All right reserved | [Privacy Policy and Upgrade Cookies](#) | Credits:  
Marchio di Fabbrica