

CHEMLEX - CHF064ENUHW

EN 12115 Chemical S&D Hose
with UPE Tube, 16 Bar



Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
CHF064ENUHW-19x6	19	31	6	16	64	80	0,66	40
CHF064ENUHW-25x6	25	37	6	16	64	120	0,82	40
CHF064ENUHW-32x6	32	44	6	16	64	160	1,05	40
CHF064ENUHW-38x6.5	38	51	6,5	16	64	215	1,47	40
CHF064ENUHW-51x7.5	51	66	7.5	16	64	330	1,80	40
CHF064ENUHW-63x8	63	79	8	16	64	425	2,38	40
CHF064ENUHW-76x8	76	92	8	16	64	650	2,89	40
CHF064ENUHW-102x8	102	118	8	16	64	860	3,55	40

Application

Chemical suction and delivery hose with UHMWPE tube for transferring a wide range of chemical products

Temperature

-35°C to +100°C

Features

Durable, long lasting, kink-free, vacuum resistant up to -1 Bar / -29 Hg, conductive

Type

Mandrel built

Tube

UHMW-PE, clear, smooth, resistant to wide range of chemicals, conductive

Reinforcement

High tensile textile cord fabric, anti-static copper wire

Cover

High temperature, weather, ozone and abrasion resistant synthetic rubber compound, black, flat corrugated, conductive

Standad/Notice

EN 12115:2021 / UHMW-PE in black available

Marking

Embossed or Transfer Label

Standards/Approvals

Comments