

DUSTRAFLEX - DAS009UX

Lightweight Abrasive Suction Hose,
3 Bar



Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
DAS009UX-51x5	51	61	5	3	9	147	1,26	40
DAS009UX-63x5	63	73	5	3	9	183	1,68	40
DAS009UX-76x5.5	76	87	5.5	3	9	228	2,30	40
DAS009UX-102x6	102	114	6	3	9	306	3,13	40
DAS009UX-127x7	127	141	7	3	9	381	4,52	40
DAS009UX-152x7.5	152	167	7.5	3	9	536	5,57	30.5

Application

Light weight suction and discharge hose for abrasive media, corrugated cover

Temperature

-30°C to +85°C

Features

Durable, flexible and kink resistant

Type

Mandrel built

Tube

Blend of synthetic and natural rubber compound, black, smooth, anti-static, high abrasion resistant according to DIN 53516: ~50mm³

Reinforcement

High tensile textile cord fabric, steel helix wire

Cover

Blend of synthetic and natural rubber compound, black, corrugated with cloth impression, anti-static, abrasion, weather and ozone resistant

Standard/Notice

Marking

Embossed or Transfer Label

Standards/Approvals

Comments