



WAM200X

Steel Reinforced Concrete Pump
Hose, 100 Bar

Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
WAM170X-38x10	38	58	10	100	200	200	2,14	40
WAM170X-51x10	51	71	10	100	200	260	2,87	40
WAM170X-60x10	63	85	10	100	200	300	3,59	40
WAM170X-65x11	65	87	11	100	200	340	4,22	40
WAM170X-76x12	76	100	12	100	200	385	5,03	40
WAM170X-80x12	80	104	12	100	200	400	5,38	40
WAM170X-102x13	102	128	13	100	200	570	6,54	40
WAM170X-114x13	114	140	13	100	200	630	8,31	40
WAM170X-127x14	127	155	14	100	200	790	9,88	40
WAM170X-152x16	152	184	16	100	200	960	12,05	30.5

Application

High pressure abrasion resistant hose with steel cord reinforcement for spraying plaster, sand, grout and mixed concrete

Temperature

-30°C to +85°C

Features

Durable and long-lasting, kink resistant, can be made to exact dimensions

Type

Mandrel built

Tube

Synthetic and natural rubber blend compound, black, smooth, highly abrasion resistant

Reinforcement

Multiple layers of steel cord plies

Cover

Synthetic and natural rubber blend compound, black, smooth with cloth impression, abrasion, ozone and weather resistant

Standard/Notice

Available with couplings and fixed lengths

Marking

Embossed or Transfer Label

Standards/Approvals

Comments