

AQUAPROFLEX-WTS009

Light Duty Water Suction and Discharge
Hose, Corrugated, 3 Bar



Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
WTS009-19x4.5	19	28	4,5	3	9	52	0,56	40
WTS009-25x5	25	35	5	3	9	70	0,63	40
WTS009-38x5.5	38	49	5,5	3	9	105	1,04	40
WTS009-51x5.5	51	62	5,5	3	9	144	1,39	40
WTS009-63x6	63	75	6	3	9	176	1,77	40
WTS009-76x6	76	88	6	3	9	229	2,48	40
WTS009-102x6.5	102	115	6.5	3	9	322	3,40	40
WTS009-127x8	127	143	8	3	9	440	4,82	40
WTS009-152x8	152	168	8	3	9	556	6,15	30.5
WTS009-203x10	203	223	11	3	9	785	8.76	30.5
WTS009-254x12	254	278	13	3	9	941	15,30	20
WTS009-305x13	305	331	13	3	9	1147	18,65	10

Application

Light duty water suction and discharge hose for use in agriculture, construction and various industrial applications

Temperature

-30°C to +85°C

Features

Flexible, suitable for vacuum of -0.6 bar

Type

Mandrel built

Tube

Synthetic or natural rubber compound, black, smooth, resistant to waste water up to 10 pH

Reinforcement

High tensile textile cord, steel helix wire

Cover

Synthetic or natural rubber compound, black, corrugated with cloth impression, weather, ozone and abrasion resistant

Standard/Notice

Cuffed ends possible on request

Marking

Embossed or Transfer Label

Standards/Approvals

Comments