

GRANULEX-DAD030

Dry Silo Delivery Hose, 10 Bar



Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
DAD030-51x5	51	61	5	10	30	100	0,96	40
DAD030-63x5	63	73	5	10	30	160	1,18	40
DAD030-76x5	76	86	5	10	30	190	1,39	40
DAD030-90x5	90	100	5	10	30	220	1,78	40
DAD030-102x5	102	112	5	10	30	266	2,03	40
DAD030-102x6.5	102	115	6.5	10	30	345	2,55	40
DAD030-127x5	127	137	5	10	30	412	3,27	40
DAD030-152x6	152	164	6	10	30	516	3,41	40
DAD030-203x6	203	215	6	10	30	620	4,66	30

Application

Dry silo delivery hose for transport of abrasive media such as cement and sand, anti-static tube compound

Temperature

-30°C to +85°C

Features

Strong, abrasion resistant tube, anti-static, durable, kink resistant

Type

Mandrel built

Tube

Blend of synthetic and natural rubber compound, black, smooth, anti-static, abrasion resistant

Reinforcement

High tensile textile cord fabric, anti-static copper wire

Cover

Blend of synthetic and natural rubber compound, black, smooth with cloth impression, anti-static, abrasion, weather and ozone resistant

Marking

Embossed or Transfer Label

Standards/Approvals

Comments