



LPH100

LPG/Oxygen Suction and
Delivery Hose, 30 Bar

Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
LPH100-25x6.5	25	38	6.5	30	100	195	0,84	40
LPH100-32x6.5	32	45	6.5	30	100	240	1,18	40
LPH100-38x7	38	52	7	30	100	315	1,39	40
LPH100-51x8	51	67	8	30	100	380	1,87	40
LPH100-63x8	63	81	8	30	100	525	2,52	40
LPH100-76x9	76	94	9	30	100	650	3,13	40

Application

Heavy duty discharge hose for transport of hydrocarbons and LPG and Oxygen products, aromatic content up to 50%

Temperature

-40°C to +100°C

Features

Durable, long lasting, resistant to aromatic content up to 50%

Type

Mandrel built

Tube

Oil resistant synthetic rubber compound, black, smooth, conductive

Reinforcement

High tensile textile cord fabric, steel wire helix, anti-static copper wire

Cover

Blend of synthetic rubber compound, black, conductive, smooth with cloth impression, oil, abrasion, weather and ozone resistant, pinpricked.

Standard/Notice

EN 1762, ISO 3821

Marking

Embossed or Transfer Label

Standards/Approvals

Comments