

PETROX - OLH048

Oil and Fuel Suction and Discharge
Hose, 16 Bar, 3:1 Safety Factor



Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
OLH048-19x5.5	19	30	5.5	16	48	82	0,72	40
OLH048-25x6	25	37	6	16	48	105	0,84	40
OLH048-32x6	32	44	6	16	48	128	0,97	40
OLH048-38x6.5	38	51	6,5	16	48	152	1,22	40
OLH048-51x7	51	67	7	16	48	210	1,83	40
OLH048-63x7	63	79	7	16	48	252	2,28	40
OLH048-76x7.5	76	92	7.5	16	48	304	2,74	40
OLH048-102x8	102	118	8	16	48	408	3,60	40
OLH048-152x11	152	174	11	16	48	625	6,20	30

Application

Suction and discharge hose for transport of mineral oil products and fuel mixtures with aromatic content up to 50%

Temperature

-40°C to +100°C

Features

Durable, long lasting, resistant to aromatic content up to 50%

Type

Mandrel built

Tube

Oil resistant synthetic rubber compound, black, smooth, anti-static

Reinforcement

High tensile textile cord fabric, steel helix wire, anti-static copper wire

Cover

Blend of synthetic rubber compound, black, anti-static, conductive, smooth with cloth impression, oil, abrasion, weather and ozone resistant and flame retardant

Standard/Notice

EN 1765 (formerly BS 1435)

Marking

Embossed or Transfer Label

Standards/Approvals

Comments