

PLASTAFLEX- WAD120

Plaster and Grout Spray Hose,
40 Bar



Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
WAD120-19x6	19	31	6	40	120	192	0,55	40
WAD120-25x6	25	37	6	40	120	231	0,71	40
WAD120-32x6	32	44	6	40	120	316	0,97	40
WAD120-35x7	35	49	7	40	120	364	1,15	40
WAD120-38x7	38	52	7	40	120	393	1,33	40
WAD120-40x7	40	54	7	40	120	420	1,48	40
WAD120-51x8	51	67	8	40	120	508	1,89	40
WAD120-51x10	51	71	10	40	120	508	2,35	40
WAD120-63x10	63	83	10	40	120	644	2,92	40
WAD120-76x10	76	96	10	40	120	688	3,27	40
WAD120-102x10	102	122	10	40	120	757	4,29	40
WAD120-127x14	127	155	14	40	120	866	7,10	40

Application

High pressure abrasion resistant hose for spraying plaster, sand, grout and mixed concrete

Temperature

-30°C to +85°C

Features

Durable and long-lasting, kink resistant, can be made to exact dimensions

Type

Mandrel built

Tube

Synthetic and natural rubber blend compound, black, smooth, highly abrasion resistant

Reinforcement

High tensile textile cord fabric and anti-static copper wire

Cover

Synthetic and natural rubber blend compound, black, smooth with cloth impression, abrasion, ozone and weather resistant

Marking

Embossed or Transfer Label

Standards/Approvals

Comments