

SOLIDEX-DAH030

Dry Silo Suction and Delivery Hose, 10 Bar



Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
DAH030-25x7	25	39	7	10	30	120	0,88	40
DAH030-32x7	32	46	7	10	30	150	1,04	40
DAH030-38x7	38	52	7	10	30	180	1,40	40
DAH030-51x7.5	51	66	7.5	10	30	230	1,98	40
DAH030-63x7.5	63	78	7.5	10	30	290	2,30	40
DAH030-76x8	76	92	8	10	30	360	3,13	40
DAH030-102x9	102	120	9	10	30	470	4,55	40
DAH030-127x11	127	149	11	10	30	580	6,64	30.5
DAH030-152x11.5	152	175	11.5	10	30	670	8.80	30.5
DAH030-203x13	203	229	13	10	30	900	13,75	30.5

Application

Suction and discharge hose for transport of abrasive media such as cement and sand, anti-static 50mm3 tube

Temperature

-30°C to +85°C

Features

Strong, wear resistant tube, anti-static, durable, kink resistant, suitable for vacuum -0.9bars

Type

Mandrel built

Tube

Blend of synthetic and natural rubber compound, black, smooth, anti-static, abrasion resistant

Reinforcement

High tensile textile cord fabric, steel helix wire, anti-static copper wire

Cover

Blend of synthetic and natural rubber compound, black, smooth with cloth impression, anti-static, abrasion, weather and ozone resistant

Marking

Embossed or Transfer Label

Standards/Approvals

Comments